

[< Вернуться к результатам](#) | [< Назад](#) 4 из 6 [Далее >](#)[Скачать](#) [Печать](#) [Сохранить в PDF](#) [Добавить в список](#) [Еще...](#)[ACS Applied Nano Materials](#) • Том 5, Выпуск 9, Страницы 13227 - 13235 • 23 September 2022**Тип документа**

Статья

Тип источника

Журнал

ISSN

25740970

DOI

10.1021/acsanm.2c02955

[Смотреть больше](#) 

Ag Nanowire/CPDMS Dual Conductive Layer Dome-Based Flexible Pressure Sensor with High Sensitivity and a Wide Linear Range

[Wang, Jiaqi^a](#); [Zhong, Yan^a](#) ; [Dai, Shengping^a](#); [Zhu, Hao^a](#); [Wu, Longgang^a](#); [Gu, Fucheng^a](#); [Cheng, Guanggui^{a,b}](#); [Ding, Jianing^{a,b}](#) [Сохранить всех в список авторов](#)^a Institute of Intelligent Flexible Mechatronics, Jiangsu University, Zhenjiang, 212013, China^b Jiangsu Collaborative Innovation Center of Photovoltaic Science and Engineering, Changzhou University, Changzhou, 213164, China281th percentile
Цитаты в Scopus1,09
FWCI 11
Количество просмотров  [Просмотреть все параметры](#) [Опции полного текста](#)  [Экспорт](#) **Краткое описание**

Ключевые слова автора

Информация химической базы данных Reaxys

Включенные в указатель ключевые слова

Темы SciVal

Параметры

Сведения о финансировании

Краткое описание

Recent research achievements for flexible pressure sensors have promoted promising applications, such as human health detection and intelligent robotics. However, striking a balance between sensitivity and linear detection range is still a challenge. In this paper, a dual conductive layer dome (DCLD) structure, where a silver (Ag) nanowire layer is used as a highly conductive layer and the composite layer of carbon black nanoparticles and polydimethylsiloxane (CPDMS) serves as a low conductive layer, is fabricated with a scratch coating process followed by dip-coating and vacuum adsorption. Benefitting from the dual conductive layer design, the sensitivity of the DCLD sensor reaches 51.7 kPa⁻¹ over an ultrawide pressure of 0.01–250 kPa, which is far better than the CPDMS single conductive layer dome (SCLD). The circuit models of DCLD and SCLD are proposed to disclose their working mechanism. The effects of carbon black nanoparticle ratio in CPDMS and the structural matching between the DCLD structure and electrode on the sensor's performance are explored. The long-cycle stability of DCLD sensors with different fabrication methods is also compared. Additionally, it has been demonstrated that the sensor is efficient in monitoring human motion, such as finger joint flexion, pulse pulses, and human breathing, showing potential in the field of human health monitoring. © 2022 American Chemical Society. All rights reserved.

Ключевые слова автора

Ag nanowires; CPDMS; dual conductive layer dome; human health detection

Цитирования в 2 документах

High-performance flexible self-powered triboelectric pressure sensor based on chemically modified micropatterned PDMS film

Zhong, Y. , Wang, J. , Han, L. (2023) *Sensors and Actuators A: Physical*

A broad range and piezoresistive flexible pressure sensor based on carbon nanotube network dip-coated porous elastomer sponge

Cai, Y. , Liu, L. , Meng, X. (2022) *RSC Advances*

[Просмотреть все 2 цитирующих документов](#)

Сообщайте мне, когда этот документ будет цитироваться в Scopus:

[Задать оповещение о цитировании](#) **Связанные документы**

Highly Sensitive and Wide-Range Flexible Bionic Tactile Sensors Inspired by the Octopus Sucker Structure

Guo, X. , Hong, W. , Liu, L. (2022) *ACS Applied Nano Materials*

Biologically Emulated Flexible Sensors With High Sensitivity and Low Hysteresis: Toward Electronic Skin to a Sense of Touch

Guo, X. , Zhou, D. , Hong, W. (2022) *Small*

Flexible pressure sensors via engineering microstructures for wearable human-machine interaction and health monitoring applications

Cui, X. , Huang, F. , Zhang, X. (2022) *iScience*

[Просмотр всех связанных документов исходя из приставных ссылок](#)

Найти дополнительные связанные документы в Scopus исходя из следующего параметра:

[Авторы](#)  [Ключевые слова](#) 

[Просмотреть сведения](#)При поддержке [Включенные в указатель ключевые слова](#)[Темы SciVal !\[\]\(de95854c7ee024cfadc48187bbb781b2_img.jpg\)](#)[Параметры](#)[Сведения о финансировании](#)[Пристатейные ссылки \(35\)](#)[Просмотреть в формате результатов поиска >](#)☐ Все[Экспорт](#) Печать Электронная почта Сохранить в PDF[Создать библиографию](#)

- ☐ 1 Wang, S., Du, X., Luo, Y., Lin, S., Zhou, M., Du, Z., Cheng, X., (...), Wang, H.
Hierarchical design of waterproof, highly sensitive, and wearable sensing electronics based on MXene-reinforced durable cotton fabrics

(2021) *Chemical Engineering Journal*, 408, art. no. 127363. Цитировано 52 раз.
www.elsevier.com/locate/ceje/publications/store/6/o/1/2/7/3/index.htm
doi: 10.1016/j.cej.2020.127363

[View at Publisher](#)

- ☐ 2 Shao, J.Y., Chen, X.L., Li, X.M., Tian, H.M., Wang, C.H., Lu, B.H.
Nanoimprint lithography for the manufacturing of flexible electronics

(2019) *Science China Technological Sciences*, 62 (2), pp. 175–198. Цитировано 67 раз.
<http://link.springer.com/journal/11431>
doi: 10.1007/s11431-018-9386-9

[View at Publisher](#)

- ☐ 3 Wang, Y., Ding, W., Mei, D.
Development of flexible tactile sensor for the envelop of curved robotic hand finger in grasping force sensing

(2021) *Measurement: Journal of the International Measurement Confederation*, 180, art. no. 109524. Цитировано 11 раз.
<https://www.journals.elsevier.com/measurement>
doi: 10.1016/j.measurement.2021.109524

[View at Publisher](#)

- ☐ 4 Xie, M., Zhu, M., Yang, Z., Okada, S., Kawamura, S.
Flexible self-powered multifunctional sensor for stiffness-tunable soft robotic gripper by multimaterial 3D printing

(2021) *Nano Energy*, 79, art. no. 105438. Цитировано 45 раз.
<http://www.journals.elsevier.com/nano-energy/>
doi: 10.1016/j.nanoen.2020.105438

[View at Publisher](#)

- 5 Sun, P., Jiang, S., Huang, Y.
Nanogenerator as self-powered sensing microsystems for safety monitoring
(2021) *Nano Energy*, 81, art. no. 105646. Цитировано 12 раз.
<http://www.journals.elsevier.com/nano-energy/>
doi: 10.1016/j.nanoen.2020.105646
View at Publisher
-
- 6 Cheng, Y., Ma, Y., Li, L., Zhu, M., Yue, Y., Liu, W., Wang, L., (...), Gao, Y.
Bioinspired Microspines for a High-Performance Spray $\text{Ti}_3\text{C}_2\text{T}_x$ MXene-Based Piezoresistive Sensor
(2020) *ACS Nano*, 14 (2), pp. 2145–2155. Цитировано 222 раз.
<http://pubs.acs.org/journal/ancac3>
doi: 10.1021/acsnano.9b08952
View at Publisher
-
- 7 Chen, X., Zeng, Q., Shao, J., Li, S., Li, X., Tian, H., Liu, G., (...), Luo, Y.
Channel-Crack-Designed Suspended Sensing Membrane as a Fully Flexible Vibration Sensor with High Sensitivity and Dynamic Range
(2021) *ACS Applied Materials and Interfaces*, 13 (29), pp. 34637–34647. Цитировано 11 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsam.1c09963
View at Publisher
-
- 8 Tang, H., Nie, P., Wang, R., Sun, J.
Piezoresistive electronic skin based on diverse bionic microstructure
(2021) *Sensors and Actuators, A: Physical*, 318, art. no. 112532. Цитировано 11 раз.
<https://www.journals.elsevier.com/sensors-and-actuators-a-physical>
doi: 10.1016/j.sna.2020.112532
View at Publisher
-
- 9 Luo, Y., Chen, X., Tian, H., Li, X., Lu, Y., Liu, Y., Shao, J.
Gecko-Inspired Slant Hierarchical Microstructure-Based Ultrasensitive Iontronic Pressure Sensor for Intelligent Interaction (Открытый доступ)
(2022) *Research*, 2022, art. no. 9852138. Цитировано 5 раз.
<https://spj.sciencemag.org/journals/research/2022/9852138/>
doi: 10.34133/2022/9852138
View at Publisher
-
- 10 Yang, C.-R., Wang, L.-J., Tseng, S.-F.
Arrayed porous polydimethylsiloxane/barium titanate microstructures for high-sensitivity flexible capacitive pressure sensors
(2022) *Ceramics International*, 48 (9), pp. 13144–13153. Цитировано 6 раз.
<https://www.journals.elsevier.com/ceramics-international>
doi: 10.1016/j.ceramint.2022.01.191
View at Publisher
-
- 11 Chen, X., Shao, J., Tian, H., Li, X., Wang, C., Luo, Y., Li, S.
Scalable Imprinting of Flexible Multiplexed Sensor Arrays with Distributed Piezoelectricity-Enhanced Micropillars for Dynamic Tactile Sensing
(2020) *Advanced Materials Technologies*, 5 (7), art. no. 2000046. Цитировано 34 раз.
[http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)2365-709X](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)2365-709X)
doi: 10.1002/admt.202000046
View at Publisher

- 12 Cai, Y.-W., Zhang, X.-N., Wang, G.-G., Li, G.-Z., Zhao, D.-Q., Sun, N., Li, F., (...), Yang, Y.
A flexible ultra-sensitive triboelectric tactile sensor of wrinkled PDMS/MXene composite films for E-skin
(2021) *Nano Energy*, 81, art. no. 105663. Цитировано 116 раз.
<http://www.journals.elsevier.com/nano-energy/>
doi: 10.1016/j.nanoen.2020.105663
View at Publisher
-
- 13 Chen, R., Luo, T., Geng, D., Shen, Z., Zhou, W.
Facile fabrication of a fast-response flexible temperature sensor via laser reduced graphene oxide for contactless human-machine interface
(2022) *Carbon*, 187, pp. 35-46. Цитировано 18 раз.
<http://www.journals.elsevier.com/carbon/>
doi: 10.1016/j.carbon.2021.10.064
View at Publisher
-
- 14 Jiang, S., Yu, J., Xiao, Y., Zhu, Y., Zhang, W.
Ultrawide Sensing Range and Highly Sensitive Flexible Pressure Sensor Based on a Percolative Thin Film with a Knoll-like Microstructured Surface
(2019) *ACS Applied Materials and Interfaces*, 11 (22), pp. 20500-20508. Цитировано 29 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsami.9b02659
View at Publisher
-
- 15 Chen, X., Sun, P., Tian, H., Li, X., Wang, C., Duan, J., Luo, Y., (...), Shao, J.
Self-healing and stretchable conductor based on embedded liquid metal patterns within imprintable dynamic covalent elastomer
(2022) *Journal of Materials Chemistry C*, 10 (3), pp. 1039-1047. Цитировано 9 раз.
<http://pubs.rsc.org/en/journals/journal/tc>
doi: 10.1039/d1tc05087g
View at Publisher
-
- 16 Zhu, J., Xue, X., Li, J., Wang, J., Wang, H., Xing, Y., Zhu, P.
Flexible pressure sensor with a wide pressure measurement range and an agile response based on multiscale carbon fibers/carbon nanotubes composite
(2022) *Microelectronic Engineering*, 257, art. no. 111750. Цитировано 2 раз.
<http://www.journals.elsevier.com/microelectronic-engineering/>
doi: 10.1016/j.mee.2022.111750
View at Publisher
-
- 17 Herren, B., Webster, V., Davidson, E., Saha, M.C., Altan, M.C., Liu, Y.
Pdms sponges with embedded carbon nanotubes as piezoresistive sensors for human motion detection
(Открытый доступ)
(2021) *Nanomaterials*, 11 (7), art. no. 1740. Цитировано 12 раз.
<https://www.mdpi.com/2079-4991/11/7/1740/pdf>
doi: 10.3390/nano11071740
View at Publisher
-
- 18 Zhu, G.-J., Ren, P.-G., Wang, J., Duan, Q., Ren, F., Xia, W.-M., Yan, D.-X.
A Highly Sensitive and Broad-Range Pressure Sensor Based on Polyurethane Mesodome Arrays Embedded with Silver Nanowires
(2020) *ACS Applied Materials and Interfaces*, 12 (17), pp. 19988-19999. Цитировано 67 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsami.0c03697
View at Publisher

- 19 Lei, D., Liu, N., Su, T., Zhang, Q., Wang, L., Ren, Z., Gao, Y.
Roles of MXene in Pressure Sensing: Preparation, Composite Structure Design, and Mechanism
(2022) *Advanced Materials*, 34 (52), art. no. 210608. Цитировано 14 раз.
[http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)1521-4095](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)1521-4095)
doi: 10.1002/adma.20210608
View at Publisher
-
- 20 Gilanizadehdizaj, G., Aw, K.C., Stringer, J., Bhattacharyya, D.
Facile fabrication of flexible piezo-resistive pressure sensor array using reduced graphene oxide foam and silicone elastomer
(2022) *Sensors and Actuators A: Physical*, 340, art. no. 113549. Цитировано 10 раз.
<https://www.journals.elsevier.com/sensors-and-actuators-a-physical>
doi: 10.1016/j.sna.2022.113549
View at Publisher
-
- 21 Gunasekaran, H.B., Ponnann, S., Zheng, Y., Laroui, A., Wang, H., Wu, L., Wang, J.
Facile Fabrication of Highly Sensitive Thermoplastic Polyurethane Sensors with Surface- and Interface-Impregnated 3D Conductive Networks
(2022) *ACS Applied Materials and Interfaces*. Цитировано 6 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsami.2c03351
View at Publisher
-
- 22 Li, W., Jin, X., Han, X., Li, Y., Wang, W., Lin, T., Zhu, Z.
Synergy of Porous Structure and Microstructure in Piezoresistive Material for High-Performance and Flexible Pressure Sensors
(2021) *ACS Applied Materials and Interfaces*, 13 (16), pp. 19211–19220. Цитировано 56 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsami.0c22938
View at Publisher
-
- 23 Han, X., Lv, Z., Ran, F., Dai, L., Li, C., Si, C.
Green and stable piezoresistive pressure sensor based on lignin-silver hybrid nanoparticles/polyvinyl alcohol hydrogel
(2021) *International Journal of Biological Macromolecules*, 176, pp. 78–86. Цитировано 29 раз.
www.elsevier.com/locate/ijbiomac
doi: 10.1016/j.ijbiomac.2021.02.055
View at Publisher
-
- 24 Du, Q., Liu, L., Tang, R., Ai, J., Wang, Z., Fu, Q., Li, C., (...), Feng, X.
High-Performance Flexible Pressure Sensor Based on Controllable Hierarchical Microstructures by Laser Scribing for Wearable Electronics (Открытый доступ)
(2021) *Advanced Materials Technologies*, 6 (9), art. no. 2100122. Цитировано 16 раз.
[http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)2365-709X](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)2365-709X)
doi: 10.1002/admt.202100122
View at Publisher
-
- 25 Yan, J., Ma, Y., Li, X., Zhang, C., Cao, M., Chen, W., Luo, S., (...), Gao, Y.
Flexible and high-sensitivity piezoresistive sensor based on MXene composite with wrinkle structure
(2020) *Ceramics International*, 46 (15), pp. 23592–23598. Цитировано 45 раз.
<https://www.journals.elsevier.com/ceramics-international>
doi: 10.1016/j.ceramint.2020.06.131
View at Publisher
-

□ 26 Guan, X., Wang, Z., Zhao, W., Huang, H., Wang, S., Zhang, Q., Zhong, D., (...), Peng, Z.
Flexible Piezoresistive Sensors with Wide-Range Pressure Measurements Based on a Graded Nest-like Architecture
(2020) *ACS Applied Materials and Interfaces*, 12 (23), pp. 26137-26144. Цитировано 64 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsami.0c03326
View at Publisher

□ 27 Geng, D., Chen, S., Chen, R., You, Y., Xiao, C., Bai, C., Luo, T., (...), Zhou, W.
Tunable Wide Range and High Sensitivity Flexible Pressure Sensors with Ordered Multilevel Microstructures
(2022) *Advanced Materials Technologies*, 7 (6), art. no. 2101031. Цитировано 7 раз.
[http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)2365-709X](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)2365-709X)
doi: 10.1002/admt.202101031
View at Publisher

□ 28 Lee, Y., Myoung, J., Cho, S., Park, J., Kim, J., Lee, H., Lee, Y., (...), Ko, H.
Bioinspired Gradient Conductivity and Stiffness for Ultrasensitive Electronic Skins
(2021) *ACS Nano*, 15 (1), pp. 1795-1804. Цитировано 56 раз.
<http://pubs.acs.org/journal/ancac3>
doi: 10.1021/acsnano.0c09581
View at Publisher

□ 29 Pang, Y., Zhang, K., Yang, Z., Jiang, S., Ju, Z., Li, Y., Wang, X., (...), Ren, T.-L.
Epidermis Microstructure Inspired Graphene Pressure Sensor with Random Distributed Spinosum for High Sensitivity and Large Linearity
(2018) *ACS Nano*, 12 (3), pp. 2346-2354. Цитировано 425 раз.
<http://pubs.acs.org/journal/ancac3>
doi: 10.1021/acsnano.7b07613
View at Publisher

□ 30 Ding, H., Zang, W., Li, J., Jiang, Y., Zou, H., Ning, N., Tian, M., (...), Zhang, L.
CB/PDMS electrodes for dielectric elastomer generator with low energy loss, high energy density and long life
(2022) *Composites Communications*, 31, art. no. 101132. Цитировано 4 раз.
<http://www.journals.elsevier.com/composites-communications>
doi: 10.1016/j.coco.2022.101132
View at Publisher

□ 31 Tang, Z.-H., Xue, S.-S., Li, Y.-Q., Zhu, Z.-C., Huang, P., Fu, S.-Y.
One-Step Synthesis of Microdome Patterns for Microstructured Pressure Sensors with Ultra-High Sensing Performance
(2021) *ACS Applied Materials and Interfaces*, 13 (40), pp. 48009-48019. Цитировано 13 раз.
<http://pubs.acs.org/journal/aamick>
doi: 10.1021/acsami.1c12241
View at Publisher

□ 32 Ruschau, G.R., Yoshikawa, S., Newnham, R.E.
Resistivities of conductive composites
(1992) *Journal of Applied Physics*, 72 (3), pp. 953-959. Цитировано 374 раз.
doi: 10.1063/1.352350
View at Publisher

□ 33 Araromi, O.A., Walsh, C.J., Wood, R.J.
(2016) *Fabrication of Stretchable Composites with Anisotropic Electrical Conductivity for Compliant Pressure Transducers*, pp. 1-3. Цитировано 2 раз.
IEEE SENSORS, 30 Oct.-3 Nov. 2016; 2016

- 34 Ezquerro, T.A., Kulesza, M., Cruz, C.S., Baltá-Calleja, F.J.
Charge transport in polyethylene–graphite composite materials
(1990) *Advanced Materials*, 2 (12), pp. 597–600. Цитировано 80 раз.
doi: 10.1002/adma.19900021209
[View at Publisher](#)

- 35 Hirata, K., Yaginuma, T., O'Rourke, M.F., Kawakami, M.
Age-related changes in carotid artery flow and pressure pulses:
Possible implications for cerebral microvascular disease
(Открытый доступ)
(2006) *Stroke*, 37 (10), pp. 2552–2556. Цитировано 122 раз.
doi: 10.1161/01.STR.0000242289.20381.f4
[View at Publisher](#)

⌘ Zhong, Y.; Institute of Intelligent Flexible Mechatronics, Jiangsu University, Zhenjiang,
China; эл. почта:zhongyan1021@163.com
© Copyright 2022 Elsevier B.V., All rights reserved.

О системе Scopus

- Что такое Scopus
- Содержание
- Блог Scopus
- Интерфейсы API Scopus
- Вопросы конфиденциальности

Язык

- Switch to English
- 日本語版を表示する
- 查看简体中文版本
- 查看繁體中文版本

Служба поддержки

- Помощь
- Обучающие материалы
- Связь с нами

ELSEVIER

Условия использования ↗ Политика конфиденциальности ↗

Авторские права © Elsevier B.V ↗. Все права защищены. Scopus ® является зарегистрированным товарным знаком Elsevier B.V. Мы используем файлы cookie, чтобы предоставлять услуги и повышать их качество, а также для индивидуального подбора содержимого. Продолжая пользоваться сайтом, вы даете согласие на использование файлов cookie ↗.

